


Antriebsrollenkits

				4 x  1 x  1 x 
72300000+20  0.6 mm		V	—	45050223  26510155  73940083 
72300000  0.8 mm		V		45050223  26510155  73940054 
72300025  0.9 mm		V		45050224  26510156  73940103 
72300026  0.9 mm	U			45050224  26510156  73940104 
72300001  1.0 mm		V		45050224  26510156  73940055 
72300002  1.0 mm	U			45050224  26510156  73940056 
72300003  1.2 mm		V		45050225  26510157  73940057 
72300004  1.2 mm	U			45050225  26510157  73940058 
72300005  1.2 mm		U		45050225  26510157  73940059 
72300006  1.4 mm	U			45050225  26510157  73940060 
72300007  1.4 mm		U		45050225  26510157  73940061 
72300014  1.4 mm		V		45050225  26510157  73940084 
72300008  1.6 mm	U			45050225  26510157  73940062 
72300009  1.6 mm		U		45050225  26510157  73940063 
72300015  1.6 mm		V		45050225  26510157  73940085 
72300010  2.0 mm	U			45050226  26510158  73940064 
72300011  2.0 mm		U		45050226  26510158  73940065 
72300016  2.0 mm		V		45050226  26510158  73940086 
72300012  2.4 mm	U			45050226  26510158  73940066 
72300013  2.4 mm		U		45050226  26510158  73940067 
72300017  2.4 mm		V		45050226  26510158  73940087 

61110100 E

Empfehlungen

V-Spur = (harte Drähte) Baustahl – Edelstahl – harte Fülldrähte - Oberflächenauftrag

U-Spur = (weiche Drähte) Aluminium – Kupfer – weiche Fülldrähte

U-Spur geriffelt = (gefettete weiche Drähte) z.B. graphitierte Fülldrähte

				4 x  1 x  1 x 
72200300  0.8 mm		45050223 	26510155 	73940300 
72200301  1.0 mm		45050224 	26510156 	73940301 
72200303  1.2 mm		45050225 	26510157 	73940303 
72200305  1.2 mm	U	45050225 	26510157 	73940305 
72200308  1.6 mm		45050225 	26510157 	73940308 
72200315  1.6 mm	U	45050225 	26510157 	73940315 
72200320  1.6 mm				

61110123

61110123