



ESE 608 DHG ES DI DUPLEX

Art. no.: 113023

Availability: active product

Fittings:

HATZ Diesel engine, 3-way fuel cock for ext. Fuelling, Folding handles, Soundproof housings, Starting battery 12V, Alternator overload protection, Operating hour meter

Technical data

Alternator	Duplex
Max. output [LTP] kVA/kW 3~	6,6 / 5,3
Prime power [PRP] kVA/kW 3~	6,0 / 4,8
Max. output [LTP] kVA/kW 1~	4,4 / 4,0
Prime power [PRP] kVA/kW 1~	4,0 / 3,6
Nominal voltage 3~	400 V 3~
Nominal voltage 1~	230 V 1~
Nominal current 3~	8,7 A 3~
Nominal current 1~	17,4 A 1~
Power factor cos (phi)	0,8 / 0,9
Frequency	50 Hz
Protection class	IP54
Engine type	Hatz 1 B 50
Number of cylinders	1
Displacement	517 ccm
Output 3000 RPM	7,6 kW
Fuel	Diesel
Tank capacity (litres)	6
Consumption l/h at 75% load	1,3
Running time (h) at 75% load	4,5
Start-up system	Electric start
Sound power level LWA db(A)	94
Sound pressure level (7 m) db(A)	69
Weight ca. (kg)	150
Dimensions L x B x H (mm)	700 x 440 x 580
Shockproof sockets	3 x 230V 16A, 1 x 400V CEE 16A
Electronic devices 230V up to	3600 W
Electronic devices 400V up to	4800 W
Electric tools 230V up to	3500 W
Electric tools 400V up to	4700 W
Gardening or construction equipment 230V up to	2400 W
Gardening or construction equipment 400V up to	3200 W
Compressors or pumps 230V up to	1800 W
Compressors or pumps 400V up to	2400 W
Inverter welding equipment up to	3,25 mm

Technische Angaben und Abbildungen sind unverbindlich. Für Druckfehler und Irrtümer übernehmen wir keine Haftung.