

Technical Data

Rating at 60% duty cycle
(10 min. cycle)

- Mixed gas: 200 A
- CO₂: 230 A

Cooling method Gas cooling

Wire diameter 0.8 - 1.2 mm

Gas flow 12 l/min

Technical specification according to IEC 60974-7

Connection Euro-Central connector
Other connectors are available upon request.

Torch rating will be reduced when using pulsed-arc power sources.



Contact tips

	Pos.		Part no.
M6	▶ 10	ECu, M6 x 28	340P__1069*
		CuCrZr, M6x28	340P__3069*
		Alu, ECu, M6x28	341P__1069*
M8	▶ 11	ECu, M8 x 30	340P__1262*
		CuCrZr, M8x30	340P__3262*
		Alu, ECu, M8x30	341P__1262*

▶ = Standard equipment

* At the blank, please insert suitable information for torch length or wire diameter, e.g. 3 for 3 m or 08 for 0.8 mm.

Tip holders

	Pos.		Part no.
M6	▶ 20	for contact tip M6	342P006003
M8	▶ 21	for contact tip M8	342P008003


Ordering information for torches

Supplied equipped for steel wire Ø 1.0 mm

TBi 250 Expert	with Euro central connector	3 m	104P321030
		4 m	104P321040
		5 m	104P321050
TBi 250 Expert	with Euro central connector and long trigger	3 m	104P3L1030
		4 m	104P3L1040
		5 m	104P3L1050

Spare parts

Pos.	Description	Part no.
50	Torch neck TBi 250, 50°	104P001008
51	Nozzle spring TBi 250/351	103P002006
52	PVC body	600P002017
60	Handle Expert cpl., gas cooled	380P230001
61	Handle Expert cpl., gas cooled, long trigger	380P230002
62	Screw for Expert handle	100P541101
63	Trigger, red, 2 poles	385P021016
64	Trigger, red, 2 poles, long	385P021018



Gas nozzle

	Pos.	Description	Part no.
	40	conical, NW 15 mm L= 56.8 mm	345P012003
	40	conical, NW 15 mm long insulation L= 56.8 mm	345P012303
	41	conical, NW 11 mm only for M6 L= 56.2 mm	345P013003
	42	cylindrical, NW 20 mm long insulation L= 56.2 mm	345P011303
	43	bottle form, NW 14 mm L= 56.2 mm	345P014003
	43	bottle form, NW 11 mm only for M6 L= 56.2 mm	345P014303
	44	spot welding nozzle NW 19 mm, long insulation L= 66.7 mm	345P015503

Pos.	Description	Part no.	Pos.	Description	Part no.
70	Coaxial cable TBi ProFlex M	361P0M11_0*	80	Cable lug, flat	375P000023
71	Hex nut M10x1	101P002005	81	Insulated connector, male, round	375P000004
72	Cable support Expert cpl., gas cooled, 'Basic'	700P001061	82	Insulated connector, female, round	375P000003
73	Adaptor nut Expert, 'Basic'	700P002161			
74	Cap for adaptor nut Expert	700P002059			
75	Central adaptor ESG cpl., 2 poles, moveable pins	701P001048			
76	Sleeve nut M10x1	701P002005			
77	O-ring 4.0x1.0 mm (gas nipple)	365P100040			
78	Screw M4x6	100P008401			