

Exhaust Set - Art. No.:79 003 201

- » Flexible operation
- » Up to 4 m reach



Applications

- » High levels of smoke and dust
- » Non-stop operation
- » Where filtration is not essential
- » Welding fumes, gases, vapours, light dusts, car exhaust fumes

Benefits

- » Very quiet due to housing of cast silumin
- » 40% less adjustment of the exhaust arm needed due to exhaust hood design
- » User-friendly due to particularly smooth movement of the hood with one hand
- » Arm keeps position due to self-supporting design

Properties

- » 360 degrees rotating exhaust hood with damper
- » Self-supported by internal springs
- » As a flexible exhaust arm: Polyester fabric hose, PVC coated with welded steel wire spiral
- » As a rigid metal tube arm: Powder-coated aluminum tube, three flexible hose sections
- » Fan made of spark-proof cast silumin

Scope of supply

- » Fan
- » Exhaust arm with hood
- » Wall bracket
- » Motor protection switch
- » Set of connecting material
- » Connecting pipe with outlet

Variants

- » Various arm lengths and versions
- » Other voltages

Technical Data

Art. No	79 003 201
Basic data	
Extraction capacity	1,000 m ³ /h
Weight	43.5 kg
Motor power	0,75 kW
Power supply	3 x 400 V / 50 Hz
Rated current	1.5 A
Noise level	73 dB(A)
Additional information	
Fan type	Radial fan
Quantity of extraction arms	1
Exhaust arm type	flexible exhaust arm
Diameter extraction arm	150 mm
Length of exhaust arm	3 m